

TECHNICAL DATA AND NOMINAL PERFORMANCES

TRIPACK

MODEL	50	66	86	112	140	180	230
	Z2	Z2	Z2	Z2	Z2	Z2	Z2
Size	J7	J7	J7	J7	J7	J7	J8

COOLING

Cooling capacity (1)	kW	50,2	66,3	86,6	113,0	141,3	182,1	235,2
Power input	kW	11,1	15,1	19,2	25,6	31,8	41,0	52,7

HEATING

Heating capacity (2)	kW	55,5	73,7	95,9	124,8	156,2	200,8	279,5
Power input	kW	11,1	15,1	19,2	25,4	31,7	40,7	52,5
Compressors	n.	2	2	2	2	2	2	2
Gas circuits	n.	1	1	1	1	1	1	1
Sound pressure (5)	dB(A)	61,0	61,0	61,0	64,0	64,0	64,0	64,0

SANITARY WATER

sanitary water production only (3)

Heating capacity	kW	55,6	73,6	96,3	124,4	156,2	201,1	259,0
------------------	----	------	------	------	-------	-------	-------	-------

contemporary production of chilled water and sanitary water (4)

Cooling capacity	kW	44,6	58,7	77,4	100,0	125,9	161,9	206,3
Heating capacity	kW	58,4	77,3	101,2	131,0	164,4	211,9	269,9

- (1) Referred to chilled water temperature 12/7°C and water to the condenser at 30°C
- (2) Referred to hot water outlet temperature 30/35°C and water outlet temperature at 5°C
- (3) Referred to sanitary water temperature 40/45°C and in/out water temperature 10/5°C
- (4) Referred to sanitary water temperature 40/45°C and chilled water outlet temperature at 7°C
- (5) Sound pressure 1m far in free field conditions according to ISO3744 norms

POWER SUPPLY: 400.3.50+N

DIMENSIONS (mm)

TRIPACK "J"

Size	a	b	c
J7	1.200	750	1.700
J8	1.800	1.200	1.740

