

# w-NEXT HD S & K

14 – 183 kW

Air conditioners for IT Cooling for chilled water feeding.  
High cooling density version.



 EC FAN

 HIGH DENSITY

 HI-TEMPERATURE



ADAPTIVE  
SET POINT



Active  
Redundancy



HIGH  
CHILLED WATER  
TEMPERATURE

The picture of the unit is indicative and may vary depending on the model

- PERIMETER INSTALLATION
- HIGH CHILLED WATER TEMPERATURE
- VARIABLE AIR AND WATER FLOW
- AIR DELIVERY FROM THE BOTTOM (UNDER)
- PLUG FANS WITH EC ELECTRIC MOTOR
- 2-WAY CHILLED WATER VALVE
- AIR SUCTION TEMPERATURE UP TO 45°C

## INDEX

MEHITS CERTIFICATIONS.....	3
GENERAL CHARACTERISTICS .....	4
INSTALLATION.....	5
PRODUCT FEATURES AND BENEFITS .....	5
MODEL IDENTIFICATION.....	5
WORKING LIMITS – W-NEXT HD S & K.....	6
STORING TEMPERATURE.....	6
MAIN COMPONENTS.....	7
OPTIONAL ACCESSORIES .....	9
TECHNICAL DATA – W-NEXT HD S.....	10
TECHNICAL DATA – W-NEXT HD K.....	12
TECHNICAL DATA – W-NEXT HD K.....	14
HIGH CHILLED WATER TEMPERATURE.....	14
HYDRAULIC DIAGRAM.....	16
2-WAY VALVE FOR CHILLED WATER FLOW CONTROL .....	16
ACOUSTIC DATA .....	17
ELECTRICAL DATA.....	17
WATER QUALITY .....	18
MICROPROCESSOR CONTROL SYSTEM.....	19
OPTIONAL ACCESSORIES – DOUBLE POWER SUPPLY WITH AUTOMATIC TRANSFER SWITCH .....	21
OPTIONAL ACCESSORIES – NETWORK ANALYZER.....	22
OPTIONAL ACCESSORIES – FIRE / SMOKE SENSORS .....	23
OPTIONAL ACCESSORIES - CONDENSATE DISCHARGE PUMP .....	24
OPTIONAL ACCESSORIES – MODULATING STEAM HUMIDIFIER.....	25
OPTIONAL ACCESSORIES – DEHUMIDIFICATION SYSTEM.....	27
OPTIONAL ACCESSORIES – 2-WAY BY-PASS VALVE FOR CHILLED WATER CIRCUIT.....	27
OPTIONAL ACCESSORIES – ELECTRIC HEATERS .....	28
OPTIONAL ACCESSORIES - FLOOR STAND .....	30
OPTIONAL ACCESSORIES - DOUBLE PANELS IN EUROCLASS A1 .....	31
OPTIONAL ACCESSORIES – EPM <sub>10</sub> 50% EFFICIENCY AIR FILTERS .....	31
OPTIONAL ACCESSORIES – NON- RETURN MOTORIZED DAMPER.....	32
OPTIONAL ACCESSORIES - PLENUM ON AIR DELIVERY/RETURN .....	34
OPTIONAL ACCESSORIES – DIRECT FREE-COOLING PLENUM .....	40
OPTIONAL ACCESSORIES – COOLNET.....	42
OPTIONAL ACCESSORIES – ADAPTIVE SET-POINT .....	42
OPTIONAL ACCESSORIES – KIPLINK – KEYBOARD IN YOUR POCKET .....	42
OPTIONAL ACCESSORIES – CLOUD PLATFORM: WEB SERVICES BASED ON CLOUD TECHNOLOGY FOR REMOTE MONITORING AND MANAGEMENT OF AIR CONDITIONING PLANTS.....	43
MACHINE DRAWINGS .....	44
HOLE IN THE RAISED FLOOR FOR DOWNFLOW VERSION .....	49
EXAMPLE FOR MACHINES NOISE EMISSION CALCULATION.....	50
VALVE PRESSURE DROP CALCULATION AS FUNCTION OF WATER FLOW RATE.....	51

## MEHITS CERTIFICATIONS



### SYSTEM CERTIFICATIONS

**ISO 9001 CERTIFICATION – MEHITS S.p.A.**  
Quality Management System



**ISO 14001 CERTIFICATION – MEHITS S.p.A.**  
Environmental Management System



**BS OHSAS 18001 CERTIFICATION – MEHITS S.p.A.**  
Occupational Health and Safety Management System

### PRODUCT CERTIFICATIONS BY COUNTRY



**CE MARKING**  
MEHITS units are in compliance with the European Directives in force.



**CCC – CQC CERTIFICATION**  
(People's Republic of China)



**EAC CERTIFICATION**  
(Russian Federation, Belarus, Kazakhstan)



## GENERAL CHARACTERISTICS



**UNDER**  
Downflow air delivery

### w-NEXT HD S: Air Conditioners for IT Cooling.

- High cooling density version;
- Chilled water feeding;
- Variable air and water flow;
- Plug fans with EC electric motor.

This series, for perimeter installation, is offered in 10 models available in the following version:

- Downflow version (Under) characterized by air intake from the top and air delivery from the bottom of the unit.

Cooling capacity: 15 ÷ 148 kW


### w-NEXT HD K: Air Conditioners for IT Cooling.

- High cooling density version;
- Operation with high chilled water temperature for the highest energy efficiency
- Chilled water feeding;
- Variable air and water flow;
- Plug fans with EC electric motor.

This series, for perimeter installation, is offered in 11 models available in the following version:

- Downflow version (Under) characterized by air intake from the top and air delivery from the bottom of the unit.

Cooling capacity: 15 ÷ 183 kW




The machines are made for indoor installation.

The constructive solutions and the internal lay-out allow high application flexibility and the frontal access to the main components for the inspection and routine maintenance.

The installation requires electrical and hydraulic connections.

Final assembly on all machines before shipment including running test, reading and monitoring of operating parameters, alarms simulation and visual check.

## INSTALLATION



### DOWNFLOW VERSION (Under)

Typical installation is on the perimeter.

The units are placed along the perimeter of the data center. Air suction from the top of the unit and air delivery in the underfloor void.

The air distribution is achieved by special tiles placed in front of the racks row, forming cold aisle for air diffusion. On the rear of the racks is expelled the hot air (hot aisle) then aspirated by the unit.

For an optimal installation is advisable to provide the cold aisle containment.

Some solutions provide a service corridor around the server rooms where to place the units. In this case it is necessary to provide the air intake plenum for each unit. With this solution all the space in the Data Center is available for the installation of racks.

### OPTIONAL

An extensive list of accessories allows the unit to adapt effectively to the real needs of the system, reducing the time and cost of installation.

## PRODUCT FEATURES AND BENEFITS

- SHR = 1;
- Optimization of the hydraulic circuit;
- New plug fans with EC electric motors with impeller in composite material, which guarantees a reduction of power consumption;
- New fans electric motor that do not require maintenance;
- Improvement of the control software with advanced control logic;
- Increased cooling density, up to 56,1 kW per m<sup>2</sup>;
- Operation with high chilled water temperature (K version) for the highest energy efficiency;
- Total front access for the routine maintenance;
- Panels fully removable to facilitate the operations of extraordinary maintenance;

## MODEL IDENTIFICATION

**Air conditioners for IT Cooling** for chilled water feeding

**model: w-NEXT HD S U 072 E5**

**w-NEXT HD**

**Series**

**S**

**Version**

S = Hi Density

K = Hi Density / Hi chilled water temperature

**U**

**Air delivery**

U = under – downflow air delivery

**072**


**Model / Cooling capacity (kW) at nominal conditions**

**E5**

**Size**



## WORKING LIMITS – w-NEXT HD S & K



### ROOM AIR CONDITIONS

Room air temperature:

14°C	minimum temperature with wet bulb.
27°C	maximum temperature with wet bulb.
18°C	minimum temperature with dry bulb.
45°C	maximum temperature with dry bulb.

### AREA "A". Machine operating envelope.

Room air humidity:

20%RH	minimum relative humidity.
60%RH	maximum relative humidity.

### CHILLED WATER TEMPERATURE

6°C	Minimum chilled water inlet temperature
25°C	Maximum chilled water inlet temperature
ΔT 3°C	Minimum temperature difference between chilled water inlet and outlet
ΔT 10°C	Maximum temperature difference between chilled water inlet and outlet

### HYDRAULIC CIRCUIT

ΔP 5-150kPa	Pressure drop range of the hydraulic circuit.
10 Bar	Maximum working pressure of the hydraulic circuit

### POWER SUPPLY

± 10%	Maximum tolerance of the supply voltage (V)
± 2%	Maximum unbalancing of the phases.

## STORING TEMPERATURE

If the machine is not installed on receipt and is stored for a long time, store it in a protected place, at temperatures ranging between -30°C and 50°C in absence of superficial condensation and direct sun light.



## MAIN COMPONENTS



### FRAMEWORK

- Base in aluminium extrusion, painted with epoxy powders. Colour RAL 9005;
- Frame in aluminium profile, painted with epoxy powders. The inner frame is provided with seals for the panels. Colour RAL 9005;
- Panels in galvanized steel sheet with protective surfaces treatment in compliance with UNI ISO 9227/ASTMB117 and ISO 7253, and painted with epoxy powders. Colour RAL 7016 hammered;
- Panels insulated with polyurethane foam and seals to ensure air tight.
- Hinged front panels with quick release removal system.
- Total front access for routine maintenance.
- Removable lateral and back side panels.
- Air flow UNDER version:
  - Air intake from the top and air delivery from the bottom.
- Compartment for electrical panel on unit front for direct access to control and regulation devices;

### FILTER SECTION

- Washable air filters with COARSE 40% efficiency (according to ISO EN 16890), with cells in synthetic fibre and metallic frame.
- Air filters access:
  - Frontal access for all machines

### COOLING SECTION

- Heat exchanger coil with internally corrugated copper tubes and high efficiency aluminium fins, specifically developed to provide high heat transfer and lower pressure drops.
- Finned pack with hydrophilic treatment that assure the condensate water drop, high thermal conductivity and does not favour the growth of micro-organisms.
- 2-way motorized valve for water flow regulation with 0=10 VDC control actuator and emergency manual control.
- Frame in galvanized steel.
- Condensate tray in peraluman with PVC flexible discharge pipe.
- Air temperature sensors upstream and downstream the cooling section, with control, regulation and limitation functions.
- Temperature probe on chilled water inlet.

### FANS SECTION

The fan section is contained within the machine and includes:

- Centrifugal fans with backward curved blades with wing profile, single suction and without scroll housings (Plug-fans), directly coupled to external rotor electric motor.
  - Impeller in composite material exempt from rust formation.
  - Brushless type synchronous EC motor with integrated electronic commutated system and continuous variation of the rotation speed. The motor rotation control is obtained with the EC system (Electronic Commutation) that manage the motor according to the signal coming from the microprocessor control.
- Fans control through ModBus. In case of failure, the control stops the interested fan indicating the type of fault. The machine with more than one fan is not stopped.
- Fan guard with rubber support (UNDER version)



### ELECTRICAL PANEL

In accordance with EN60204-1 norms, suitable for indoor installation, complete with:

- Main switch with door lock safety on frontal panel;
- Magnetothermic switches for supply fans.  
The supply fans equipped with EC electric motor and don't require contactors.
- Transformer for auxiliary circuit and microprocessor supply.

- Terminals:

#### OUTLETS

- Voltage free deviating contact for General Alarm 1-2
- Voltage free contact for supply fans status.
- Voltage free contact for smoke / fire sensor (the sensors are accessory)

#### INLETS

- External enabling.
- Power supply 400/3+N/50.



### CONTROL SYSTEM

Microprocessor control system with graphic display for control and monitor of operating and alarms status.

The system includes:

- Built-in clock for alarms date and time displaying and storing;
- Built-in memory for the storing of the intervened events (up to 200 events recorded);
- Integrated connectivity port MBUS RS485/JBUS;
- Predisposition for additional connectivity board housing (MBUS RS485/JBUS, MBUS RS232/JBUS for GSM modem, LON, BACnet for Ethernet (SNMP- TCP/IP), BACnet for MS/TP). The electronic cards are optional accessories.
- Main components hour-meter;
- Non-volatile "Flash" memory for data storage in case of power supply faulty;
- Menu with protection password;
- LAN connection (max 10 units).



## OPTIONAL ACCESSORIES

The descriptions of these additional components can be found in Chapter OPTIONAL ACCESSORIES.

- Double power supply with automatic change-over. Not compatible with “oversized electric heaters” and “oversized humidifier” optional accessories.
- Network analyzer: multifunction utility for calculating and displaying the machine electrical measurements.
- Smoke sensor. Supplied in mounting kit.
- Fire sensor. Supplied in mounting kit.
- Condensate drain system. Supplied in mounting kit. The system includes pump with activation float and 10 linear meters long discharge pipe.
- Modulating steam humidifier with immersed electrodes with electronic control. The optional foresee the combined Temperature / Humidity sensor on return air.
- Dehumidification system. The optional foresee the combined Temperature / Humidity sensor on return air.
- 2-way motorized valve with 0÷10 VDC control actuator and emergency manual control for the third way (by-pass) of the chilled water hydraulic circuit. The valve is in combination with the main water flow control valve.
- Electric heating system consisting of aluminium armoured elements with integral fins
- Unit floor stand with height adjusting rubber holders. It is not possible to match the unit floor stand with plenum installed under the machine.
- Double panels in Euroclass A1.
- Washable air filter with ePM<sub>10</sub> 50% efficiency (according to ISO EN 16890). Not compatible with plenum with ePM<sub>2.5</sub> 50%, ePM<sub>1</sub> 50%, ePM<sub>1</sub> 85% efficiency filters on air delivery.
- Non-return air damper driven by electric servomotor installed on the machine air return.
- Empty plenum. Available in Euroclass A1.
- Plenum with noise absorption partitions on air delivery.
- Plenum with ePM<sub>2.5</sub> 50%, ePM<sub>1</sub> 50%, ePM<sub>1</sub> 85% efficiency filters on air delivery. Not compatible with washable air filter with ePM<sub>10</sub> 50% efficiency.
- Air distribution plenum with double row adjustable grille on front side. Available in Euroclass A1.
- Air distribution plenum with double row adjustable grilles on three sides. Available in Euroclass A1.
- Air distribution plenum with double row adjustable grille on front side and noise absorption partitions.
- Plenum for direct free-cooling on air intake. The optional foresee the combined Temperature / Humidity sensor on machine air suction and the Temperature sensor for ambient air.
- COOLNET: application software to maximize energy saving in Load Sharing.
- ADAPTIVE SET POINT: software that optimizes the operation of liquid chillers connected to the indoor air conditioners by control of the effective room thermal load.
- KIP LINK: Keyboard in your pocket. Allows to operate on the unit with smartphone or tablet.
- CLOUD PLATFORM: Web services based on cloud technology for remote monitoring and management.

### OTHER ACCESSORIES

- Automatic system for the air pressure control in the under floor. The system controls the supply fans rotation speed in order to keep constant the air pressure in the under floor via a differential pressure transmitter connected to the microprocessor control.
- Differential pressure switch on the air side for clogged filters alarm signal.
- Under floor water alarm through sensor to be placed on the floor.
- Additional underfloor water sensor kit.
- Combined Temperature / Humidity sensor on return air.
- Temperature sensor for outdoor installation.
- Combined Temperature / Humidity sensor for remote installation. The optional is added to the standard sensor on machine air suction.
- Microprocessor control accessories:
  - Remote terminal.
  - Serial card MBUS RS485/JBUS.
  - Serial card MBUS RS232/JBUS for GSM modem.
  - Serial card LON.
  - Serial card BACnet for Ethernet – SNMP – TCP/IP.
  - Serial card BACnet for MS/TP.
  - Temporary microprocessor power supply. The system guarantees the microprocessor power supply for a few minutes, in case of supply voltage failure.
  - Analogue set point compensation according to an external analogue signal at Customer care.  
The microprocessor control, through the additional module “expansion card”, can manage a compensation signal of the return air setpoint by analogue input (0...1V; 0...5V; 0,5...4,5V; 4...20mA; 0...20mA). The compensation curve allows to assign a temperature setpoint offset respectively to the minimum and maximum signal managed by the input.

### **WARNING**

The Manufacturer reserves the right to accept the matching of the optional installed on the machine.

## TECHNICAL DATA – w-NEXT HD S

MODEL		015	024	041	048	060
SIZE		E1	E2	E3	E3P	E4
VERSION (1)		U	U	U	U	U
<b>COOLING CAPACITY (2)</b>						
Total	kW	15,4	25	39,4	48,5	61,6
Sensible	kW	12,7	21,1	32,7	40,8	52
SHR (3)		0,82	0,84	0,83	0,84	0,84
"EC" SUPPLY FANS	n.	1	1	1	1	1
Air flow	m <sup>3</sup> /h	3250	5560	8300	10500	13600
Nominal external static pressure	Pa	20	20	20	20	20
Maximum external static pressure	Pa	42	65	533	425	155
Fans power input (4)	kW	0,33	0,89	1,43	1,8	2,23
<b>COOLING COIL</b>						
Water flow rate (2)	m <sup>3</sup> /h	2,66	4,32	6,76	8,35	10,62
dP coil + valve (2)	kPa	29,3	66	75,3	59,2	70,8
Water volume	l	4,2	5,3	7,8	11,4	13,8
AIR FILTERS	n.	-	-	-	-	-
Filter area	m <sup>2</sup>	0,89	1,15	1,76	2,06	2,59
Efficiency (ISO EN 16890)	COARSE	60%	60%	60%	60%	60%
POWER SUPPLY	V/Ph/Hz	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
<b>ENERGY EFFICIENCY INDEX (2)</b>						
EER Energy Efficiency Ratio	kW/kW	46,7	28,1	27,6	26,9	27,6
<b>DIMENSIONS</b>						
Length	mm	650	785	1085	1085	1305
Width	mm	675	675	775	930	930
Height	mm	1925	1925	1925	1925	1980
NET WEIGHT UNDER	kg	216	257	325	329	379
<b>HYDRAULIC CONNECTIONS</b>						
WATER INLET / OUTLET ISO 7/1 - R	Ø	1"	1+1/4"	1+1/2"	1+1/2"	2"
WATER INLET / OUTLET – DN – PN10 (5)	Ø mm	-	-	-	-	-
<b>CONDENSATE DISCHARGE</b>						
Rubber pipe – internal diameter	Ø mm	19	19	19	19	19

### THE COOLING CAPACITY DOES NOT CONSIDER THE SUPPLY FAN MOTOR THERMAL LOAD

1. U = Under, downflow
2. Gross value. Characteristics referred to entering air at 24°C-50%RH with chilled water temperature 7-12°C - 0% glycol. ESP=20Pa.
3. SHR = Sensible cooling capacity / Total cooling capacity.
4. Corresponding to the nominal external static pressure
5. The counter-flange is not supplied. It is at Customer charge

# w-NEXT HD S & K

## TECHNICAL DATA – w-NEXT HD S

MODEL		072	090	110	122	146
SIZE		E5	E6	E7	E8	E9
VERSION (1)		U	U	U	U	U
<b>COOLING CAPACITY (2)</b>						
Total	kW	74	92,6	114	128	148
Sensible	kW	71,1	78,1	95,2	106	124
SHR (3)		0,85	0,84	0,84	0,83	0,84
"EC" SUPPLY FANS	n.	2	2	2	3	3
Air flow	m <sup>3</sup> /h	16800	20500	24300	26500	31500
Nominal external static pressure	Pa	20	20	20	20	20
Maximum external static pressure	Pa	509	426	268	431	399
Fans power input (4)	kW	2,96	3,64	3,81	4,88	5,67
<b>COOLING COIL</b>						
Water flow rate (2)	m <sup>3</sup> /h	12,74	15,94	19,58	21,99	25,56
dP coil + valve (2)	kPa	40,7	65,2	102	85,1	78,8
Water volume	l	18,1	21,2	24,6	28,5	33,8
<b>AIR FILTERS</b>						
Filter area	m <sup>2</sup>	3,33	3,9	4,62	5,24	6,13
Efficiency (ISO EN 16890)	COARSE	60%	60%	60%	60%	60%
POWER SUPPLY	V/Ph/Hz	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
<b>ENERGY EFFICIENCY INDEX (2)</b>						
EER Energy Efficiency Ratio	kW/kW	25,0	25,4	29,9	26,2	26,1
<b>DIMENSIONS</b>						
Length	mm	1630	1875	2175	2499	2899
Width	mm	930	930	930	930	930
Height	mm	1980	1980	1980	1980	1980
NET WEIGHT UNDER	kg	470	531	589	660	753
<b>HYDRAULIC CONNECTIONS</b>						
WATER INLET / OUTLET ISO 7/1 - R	Ø	2"	2+1/2"	2+1/2"	3"	3"
WATER INLET / OUTLET – DN – PN10 (5)	Ø mm	-	-	-	-	-
<b>CONDENSATE DISCHARGE</b>						
Rubber pipe – internal diameter	Ø mm	19	19	19	19	19

### THE COOLING CAPACITY DOES NOT CONSIDER THE SUPPLY FAN MOTOR THERMAL LOAD

1. U = Under, downflow
2. Gross value. Characteristics referred to entering air at 24°C-50%RH with chilled water temperature 7-12°C - 0% glycol. ESP=20Pa.
3. SHR = Sensible cooling capacity / Total cooling capacity.
4. Corresponding to the nominal external static pressure
5. The counter-flange is not supplied. It is at Customer charge

## TECHNICAL DATA – w-NEXT HD K

MODEL		015	024	041	048	060	072
<b>SIZE</b>		E1	E2	E3	E3P	E4	E5
<b>VERSION (1)</b>		U	U	U	U	U	U
<b>COOLING CAPACITY (2)</b>							
<b>Total</b>	kW	15,3	24,8	38,6	48,2	62,1	76,8
<b>Sensible</b>	kW	15,3	24,8	38,6	48,2	62,1	76,8
SHR (3)		1	1	1	1	1	1
<b>"EC" SUPPLY FANS</b>	n.	1	1	1	1	1	2
Air flow	m³/h	3150	5500	8300	10500	13600	16800
Nominal external static pressure	Pa	20	20	20	20	20	20
Maximum external static pressure	Pa	56	59	521	402	128	485
Fans power input (4)	kW	0,31	0,91	1,46	1,88	2,35	3,11
<b>COOLING COIL</b>							
Water flow rate (2)	m³/h	2,62	4,28	6,66	8,31	10,69	13,24
dP coil + valve (2)	kPa	51,4	31,8	43,2	55,4	45,5	49,8
Water volume	l	6,3	7,9	11,7	17,2	20,8	27,2
<b>AIR FILTERS</b>	n.	-	-	-	-	-	-
Filter area	m²	0,89	1,15	1,76	2,06	2,59	3,33
Efficiency (ISO EN 16890)	COARSE	60%	60%	60%	60%	60%	60%
<b>POWER SUPPLY</b>	V/Ph/Hz	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
<b>ENERGY EFFICIENCY INDEX (2)</b>							
EER Energy Efficiency Ratio	kW/kW	49,4	27,3	26,4	25,6	26,4	24,7
<b>DIMENSIONS</b>							
Length	mm	650	785	1085	1085	1305	1630
Width	mm	675	675	775	930	930	930
Height	mm	1925	1925	1925	1925	1980	1980
<b>NET WEIGHT UNDER</b>	kg	220	261	332	330	385	478
<b>HYDRAULIC CONNECTIONS</b>							
WATER INLET / OUTLET ISO 7/1 - R	Ø	1"	1+1/4"	1+1/2"	1+1/2"	2"	2"
WATER INLET / OUTLET – DN – PN10 (5)	Ø mm	-	-	-	-	-	-
<b>CONDENSATE DISCHARGE</b>							
Rubber pipe – internal diameter	Ø mm	19	19	19	19	19	19

### THE COOLING CAPACITY DOES NOT CONSIDER THE SUPPLY FAN MOTOR THERMAL LOAD

1. U = Under, downflow
2. Gross value. Characteristics referred to entering air at 26°C-40%RH with chilled water temperature 10-15°C - 0% glycol. ESP=20Pa.
3. SHR = Sensible cooling capacity / Total cooling capacity.
4. Corresponding to the nominal external static pressure
5. The counter-flange is not supplied. It is at Customer charge

# w-NEXT HD S & K

## TECHNICAL DATA – w-NEXT HD K

MODEL		090	110	122	146	170
SIZE		E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U
<b>COOLING CAPACITY (2)</b>						
Total	kW	94,7	111	122	144	183
Sensible	kW	94,7	111	122	144	183
SHR (3)		1	1	1	1	1
"EC" SUPPLY FANS	n.	2	2	3	3	3
Air flow	m <sup>3</sup> /h	20500	24300	26500	31500	39600
Nominal external static pressure	Pa	20	20	20	20	20
Maximum external static pressure	Pa	420	241	413	376	151
Fans power input (4)	kW	3,68	4,03	5,04	5,9	6,93
<b>COOLING COIL</b>						
Water flow rate (2)	m <sup>3</sup> /h	16,3	19,08	21,02	24,8	31,46
dP coil + valve (2)	kPa	52,7	40,5	51,3	54,9	92,1
Water volume	l	31,8	36,8	42,7	50,6	63
<b>AIR FILTERS</b>						
Filter area	m <sup>2</sup>	3,9	4,62	5,24	6,13	6,13
Efficiency (ISO EN 16890)	COARSE	60%	60%	60%	60%	60%
POWER SUPPLY	V/Ph/Hz	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
<b>ENERGY EFFICIENCY INDEX (2)</b>						
EER Energy Efficiency Ratio	kW/kW	25,7	27,5	24,2	24,4	26,4
<b>DIMENSIONS</b>						
Length	mm	1875	2175	2499	2899	3510
Width	mm	930	930	930	930	930
Height	mm	1980	1980	1980	1980	1980
NET WEIGHT UNDER	kg	540	598	669	764	930
<b>HYDRAULIC CONNECTIONS</b>						
WATER INLET / OUTLET ISO 7/1 - R	Ø	2+1/2"	2+1/2"	3"	3"	-
WATER INLET / OUTLET – DN – PN10 (5)	Ø mm	-	-	-	-	80
<b>CONDENSATE DISCHARGE</b>						
Rubber pipe – internal diameter	Ø mm	19	19	19	19	19

### THE COOLING CAPACITY DOES NOT CONSIDER THE SUPPLY FAN MOTOR THERMAL LOAD

1. U = Under, downflow
2. Gross value. Characteristics referred to entering air at 26°C-40%RH with chilled water temperature 10-15°C - 0% glycol. ESP=20Pa.
3. SHR = Sensible cooling capacity / Total cooling capacity.
4. Corresponding to the nominal external static pressure
5. The counter-flange is not supplied. It is at Customer charge



## TECHNICAL DATA – w-NEXT HD K High chilled water temperature



MODEL		015	024	041	048	060	072
SIZE		E1	E2	E3	E3P	E4	E5
VERSION (1)		U	U	U	U	U	U
<b>COOLING CAPACITY (2)</b>							
Total	kW	14,3	23,2	35,9	44,9	57,8	71,7
Sensible	kW	14,3	23,2	35,9	44,9	57,8	71,7
SHR (3)		1	1	1	1	1	1
"EC" SUPPLY FANS	n.	1	1	1	1	1	2
Air flow	m <sup>3</sup> /h	3150	5500	8300	10500	13600	16800
Nominal external static pressure	Pa	20	20	20	20	20	20
Maximum external static pressure	Pa	56	59	521	402	128	485
Fans power input (4)	kW	0,31	0,91	1,46	1,88	2,35	3,11
<b>COOLING COIL</b>							
Water flow rate (2)	m <sup>3</sup> /h	1,54	2,52	3,88	4,86	6,22	7,74
dP coil + valve (2)	kPa	19	11,5	15,8	20	16,6	17,9
Water volume	l	6,3	7,9	11,7	17,2	20,8	27,2
<b>AIR FILTERS</b>							
Filter area	m <sup>2</sup>	0,89	1,15	1,76	2,06	2,59	3,33
Efficiency (ISO EN 16890)	COARSE	60%	60%	60%	60%	60%	60%
POWER SUPPLY	V/Ph/Hz	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
<b>ENERGY EFFICIENCY INDEX (2)</b>							
EER Energy Efficiency Ratio	kW/kW	46,1	25,5	24,6	23,9	24,6	23,1
<b>DIMENSIONS</b>							
Length	mm	650	785	1085	1085	1305	1630
Width	mm	675	675	775	930	930	930
Height	mm	1925	1925	1925	1925	1980	1980
NET WEIGHT UNDER	kg	220	261	332	330	385	478
<b>HYDRAULIC CONNECTIONS</b>							
WATER INLET / OUTLET ISO 7/1 - R	Ø	1"	1+1/4"	1+1/2"	1+1/2"	2"	2"
WATER INLET / OUTLET – DN – PN10 (5)	Ø mm	-	-	-	-	-	-
<b>CONDENSATE DISCHARGE</b>							
Rubber pipe – internal diameter	Ø mm	19	19	19	19	19	19

### THE COOLING CAPACITY DOES NOT CONSIDER THE SUPPLY FAN MOTOR THERMAL LOAD

1. U = Under, downflow
2. Gross value. Characteristics referred to entering air at 35°C-30%RH with chilled water temperature 18-26°C - 0% glycol. ESP=20Pa.
3. SHR = Sensible cooling capacity / Total cooling capacity.
4. Corresponding to the nominal external static pressure
5. The counter-flange is not supplied. It is at Customer charge



## w-NEXT HD S & K

### TECHNICAL DATA – w-NEXT HD K High chilled water temperature




MODEL		090	110	122	146	170
SIZE		E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U
<b>COOLING CAPACITY (2)</b>						
Total	kW	87,9	102	113	133	169
Sensible	kW	87,9	102	113	133	169
SHR (3)		1	1	1	1	1
"EC" SUPPLY FANS	n.	2	2	3	3	3
Air flow	m <sup>3</sup> /h	20500	24300	26500	31500	39600
Nominal external static pressure	Pa	20	20	20	20	20
Maximum external static pressure	Pa	420	241	413	376	151
Fans power input (4)	kW	3,68	4,03	5,04	5,9	6,93
<b>COOLING COIL</b>						
Water flow rate (2)	m <sup>3</sup> /h	9,46	11,05	12,24	14,36	18,28
dP coil + valve (2)	kPa	19,4	14,3	18,4	19,1	32,4
Water volume	l	31,8	36,8	42,7	50,6	63
AIR FILTERS	n.	-	-	-	-	-
Filter area	m <sup>2</sup>	3,9	4,62	5,24	6,13	6,13
Efficiency (ISO EN 16890)	COARSE	60%	60%	60%	60%	60%
POWER SUPPLY	V/Ph/Hz	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
<b>ENERGY EFFICIENCY INDEX (2)</b>						
EER Energy Efficiency Ratio	kW/kW	23,9	25,3	22,4	22,5	24,4
<b>DIMENSIONS</b>						
Length	mm	1875	2175	2499	2899	3510
Width	mm	930	930	930	930	930
Height	mm	1980	1980	1980	1980	1980
NET WEIGHT UNDER	kg	540	598	669	764	930
<b>HYDRAULIC CONNECTIONS</b>						
WATER INLET / OUTLET ISO 7/1 - R	Ø	2+1/2"	2+1/2"	3"	3"	-
WATER INLET / OUTLET – DN – PN10 (5)	Ø mm	-	-	-	-	80
<b>CONDENSATE DISCHARGE</b>						
Rubber pipe – internal diameter	Ø mm	19	19	19	19	19

#### THE COOLING CAPACITY DOES NOT CONSIDER THE SUPPLY FAN MOTOR THERMAL LOAD

1. U = Under, downflow
2. Gross value. Characteristics referred to entering air at 35°C-30%RH with chilled water temperature 18-26°C - 0% glycol. ESP=20Pa.
3. SHR = Sensible cooling capacity / Total cooling capacity.
4. Corresponding to the nominal external static pressure
5. The counter-flange is not supplied. It is at Customer charge

## HYDRAULIC DIAGRAM

Below hydraulic diagram referred to the standard configuration without optional.



## 2-WAY VALVE FOR CHILLED WATER FLOW CONTROL



The water flow control in the finned coil is achieved through a **2-way modulating ball valve with equal percentage flow control** ensured by the integrated characterizing disc.

This type of valve offers the following series of benefits:

- Equal percentage flow control.
- Closing seal with leakage rate in Class A (EN 12266-1)
- No peaks initial flow.
- Excellent stability control thanks to the integrated characterizing disc.
- Closing pressure very high.
- Excellent characteristic in partialisation.
- Stability in control.
- Wide operating pressures which provide an optimal adjustment of the water flow even under extreme conditions.
- Maintenance free.
- Self-cleaning.

The rotative actuator is controlled by a signal 0 ... 10VDC from the microprocessor controller. The actuator is equipped with an emergency button for manual operation and is maintenance-free.

## ACOUSTIC DATA

Acoustic data of the standard machine at full load working conditions.

### **WARNING:**

In a closed room the noise produced by a sound source reaches the listener in two different ways:

- Directly
- Reflected from the surrounding walls, floor, ceiling, from furniture.

With the same sound source, the noise produced in a closed room is greater than that produced outdoors. In fact, the sound pressure level generated by the source, must be added to the one reflected from the room. Also, the shape of the room affects the sound.

### w-NEXT HD S

MODEL		015	024	041	048	060	072	090	110	122	146
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9
<b>SOUND LEVEL (1)</b>											
On air delivery Under	dB(A)	67,4	76,8	77,2	78,3	79,9	80,2	80,7	80,7	83,1	83,1
On air intake Under	dB(A)	57,9	62,5	63,2	65,7	67,3	66,1	68,1	68,0	68,9	70,4
On front side Under	dB(A)	49	53	54	56	58	57	59	59	59	61

### w-NEXT HD K

MODEL		015	024	041	048	060	072	090	110	122	146	170
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
<b>SOUND LEVEL (1)</b>												
On air delivery Under	dB(A)	66,7	76,3	77,0	78,3	79,9	80,3	80,7	80,8	83,1	83,0	84,1
On air intake Under	dB(A)	57,3	62,0	62,8	65,6	67,3	66,1	68,1	68,1	68,9	70,4	71,5
On front side Under	dB(A)	48	53	53	56	58	57	59	59	59	61	62

1. Noise pressure level at 1 meter in free field – ISO 3744

## ELECTRICAL DATA

### w-NEXT HD S

MODEL		015	024	041	048	060
SIZE		E1	E2	E3	E3P	E4
VERSION (1)		U	U	U	U	U
Power supply		400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
Maximum current input	A	0,33	1,7	4,2	4,43	4,15

MODEL		072	090	110	122	146
SIZE		E5	E6	E7	E8	E9
VERSION (1)		U	U	U	U	U
Power supply		400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
Maximum current input	A	8,4	8,86	8,3	12,6	13,3

### w-NEXT HD K

MODEL		015	024	041	048	060	072
SIZE		E1	E2	E3	E3P	E4	E5
VERSION (1)		U	U	U	U	U	U
Power supply		400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
Maximum current input	A	0,33	1,7	4,2	4,43	4,15	8,4

MODEL		090	110	122	146	170
SIZE		E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U
Power supply		400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
Maximum current input	A	8,86	8,3	12,6	13,3	12,5

1. U = Under, downflow

### **WARNING:**

The electric data indicated are referred to the indoor unit. Optional accessory electric data are included within the dedicated chapters and must be added. Please refer to ELCA WORLD selection program to calculate the electrical data of the air conditioner according to the requested optional accessories.

## WATER QUALITY

For a correct and optimal functioning of the hydraulic circuits (chilled water and heating water), a water quality must be guaranteed as indicated in the table below.

The values shown in the table must be guaranteed during the entire life cycle of the machine.

	Description	Symbol	Range
1	Hydrogen ions	pH	7.5 ÷ 9
2	Presence of calcium (Ca) and magnesium (Mg)	Hardness	4 ÷ 8.5 °D
3	Chlorine ions	Cl <sup>-</sup>	< 150 ppm
4	Iron ions	Fe <sup>3+</sup>	< 0.5 ppm
5	Manganese ions	Mn <sup>2+</sup>	< 0.05 ppm
6	Carbon dioxide	CO <sub>2</sub>	< 10 ppm
7	Hydrogen sulphide	H <sub>2</sub> S	< 50 ppb
8	Oxygen	O <sub>2</sub>	< 0.1 ppm
9	Chlorine	Cl <sub>2</sub>	< 0.5 ppm
10	Ammonia	NH <sub>3</sub>	< 0.5 ppm
11	Ratio between carbonates and sulphates	HCO <sub>3</sub> <sup>-</sup> /SO <sub>4</sub> <sup>2-</sup>	> 1
12	Sulphate ions	SO <sub>4</sub> <sup>-</sup>	< 100 ppm
13	Phosphate ions	PO <sub>4</sub> <sup>3-</sup>	< 2.0 ppm

where:  $1/1.78^{\circ}\text{D} = 1^{\circ}\text{Fr}$  with  $1^{\circ}\text{Fr} = 10 \text{ gr CaCO}_3 / \text{m}^3$

ppm = parts for millions

ppb = part for billion

### Explanatory notes:

- ref.1: A greater concentration of hydrogen ions (pH) than 9 implies a high risk of deposits, whereas a lower pH than 7 implies a high risk of corrosion.
- ref.2: The hardness measures the amount of Ca and Mg carbonate dissolved in the water with a temperature lower than 100°C (temporary hardness). A high hardness implies a high risk of deposits.
- ref.3: The concentration of chloride ions with higher values than those indicated causes corrosion.
- ref. 4 - 5 - 8: The presence of iron and manganese ions and oxygen leads to corrosion.
- ref.6 - 7: Carbon dioxide and hydrogen sulphide are impurities that promote corrosion.
- ref.9: Usually in water from the waterworks it is a value of between 0.2 and 0.3 ppm. High values cause corrosion.
- ref.10: The presence of ammonia reinforces the oxidising power of oxygen
- ref.11: Below the value shown in the table, there is a risk of corrosion due to the trigger of galvanic currents between copper and other less noble metals.
- ref.12: The presence of sulphates ions triggers corrosion phenomenon.
- ref.13: The presence of phosphates ions triggers corrosion phenomenon.

It is necessary to carry out periodic checks, with withdrawals at different points of the hydraulic system.

During the first year of operation, checks are recommended every 4 months which can be reduced every 6 months starting from the second year of operation.

### WARNING:

**It is necessary that, in the presence of dirty and / or aggressive waters, an intermediate heat exchanger is installed upstream of the heat exchangers**

## MICROPROCESSOR CONTROL SYSTEM



The microprocessor control system is equipped with 6 keys terminal and back lighted graphic display on which all information in different languages or easily identifiable symbols are displayed. The system disposes of a "flash" memory that preserves the information even in absence of power supply. Part of memory is dedicated to the registration of intervened events - up to 200 events.


### KEYBOARD FUNCTIONS

	ALARM	Alarm, Back-red light active – alarm presence, push to have alarm description. If more than one alarm(s), the others can be scrolled by Key UP / DOWN
	PRG	Menu list, scrolled by key UP/DOWN: <b>Unit; Set-point; In/Out; Clock; History; User; Service; Factory.</b> Use the ENTER key to execute the mode.
	ESC	Home. Used to come back to the previous menu level or to the main screen.
	UP DOWN	Used to change the pages and values of sets. When display is in main screen (HOME), pressing one of them (UP/DOWN) will display the synoptic of the main controls.
	ENTER	Moving the cursor on adjustable Program(s) fields, to confirm the changes, press the key (ENTER) to get out of the fields.

### CONNECTIVITY

Through the optional serial port, the microprocessor control enables communication with the modern buildings BMS systems with the following protocols:

- MBUS/JBUS (RS485) serial card;
- MBUS/JBUS (RS232) for GSM modem serial card;
- LON Works serial card;
- BACnet per Ethernet – SNMP – TCP/IP serial card;
- BACnet per MS/TP serial card;



## PASSWORD

- Level 1: On request of the End User. Allowing to reach USER menu
- Level 2: Asks to Service: Allowing to reach SERVICE menu
- Level 3: Asks to Service: Allowing to reach FACTORY menu

No passwords request to enter: UNIT, SETPOINT, IN/OUT, CLOCK, HISTORY menu

## LAN NETWORK


The LAN is part of the control software and it is possible to connect up to 10 units.

This type of connection allows to control the units in coherent way, moreover the units can be controlled and managed from a shared remote terminal.

Electrical connections are on electrical panel connecting terminals.

## LAN ADDRESS LIST

Unit #	1	2	3	4	5	6	7	8	9	10	Remote Terminal
Mother board address	1	2	3	4	5	6	7	8	9	10	--
Terminal address	11	12	13	14	15	16	17	18	19	20	32



The unit connection to the local network (LAN) allows to perform the following functions:

- Balancing the operating hours among the different units by rotating the reserve units (Stand-by)
- Turning on the reserve units in case other units should turn off due to an alarm, maintenance or power feed interruption
- Turning on reserve units to offset the excessive thermal load
- Checking up to 10 units with a single user terminal (shared user terminal)



## OPTIONAL ACCESSORIES – DOUBLE POWER SUPPLY WITH AUTOMATIC TRANSFER SWITCH



The optional is not compatible with “oversized electric heaters” and “oversized humidifier” optional accessories.

The motorised changeover switches automatically manage changeover under load between two three-phase power supplies, or manually for emergency operations.

**These transfer switching (TSE) devices are suitable for low voltage systems with interruption of the supply to the load during transfer.**

The model supplied in the automatic version checks the source and switches over automatically, based on configurable parameters.

**OPEN TRANSITION TYPE TRANSFER SWITCH WITH A MINIMUM INTERRUPTION OF THE SUPPLY DURING TRANSFER.**


To maintain the microprocessor powered and avoid its restarts is mandatory to foresee the installation of the “temporary microprocessor power supply” optional accessory. The system guarantees the microprocessor power supply for a few minutes, in case of supply voltage failure.

### ATS INSTALLATION

Frame	Power Supply	ATS Installation
E1	400/3+N/50	EXTERNAL, supplied in kit
E2	400/3+N/50	EXTERNAL, supplied in kit
E3	400/3+N/50	EXTERNAL, supplied in kit
E4	400/3+N/50	EXTERNAL, supplied in kit
E5	400/3+N/50	INTERNAL (on unit electrical panel)
E6	400/3+N/50	INTERNAL (on unit electrical panel)
E7	400/3+N/50	INTERNAL (on unit electrical panel)
E8	400/3+N/50	INTERNAL (on unit electrical panel)
E9	400/3+N/50	INTERNAL (on unit electrical panel)
E10	400/3+N/50	INTERNAL (on unit electrical panel)



### KIT FOR EXTERNAL INSTALLATION



### OPTIONAL ACCESSORIES – NETWORK ANALYZER



The optional is installed within the electrical box downstream the main switch with door safety lock:

- Network transducer;
- Current transformers, one for each power supply phase cable.

This device provides continuous measurement of power consumption, monitoring current, voltage and power. These values are sent to unit microprocessor via RS485 serial cable, as shown on the unit wiring diagram.

The displayed variables are:

- Phase to phase voltage, only for three-phase units;
- Phase voltage (phase-neutral);
- Phase current;
- Neutral current only for three-phase units;
- Active phase power, only for three-phase units;
- Total active power;
- Active energy;
- Hour counts

## OPTIONAL ACCESSORIES – FIRE / SMOKE SENSORS

Is possible to install one or both of the following sensors. Sensors are supplied in mounting kit. Installation within the room at customer care.



### SMOKE DETECTOR

The optical smoke detector senses the presence of combustion by-products (visible smoke) and activates an alarm.

The operating principle is based on the light scattering technique (Tyndall effect).

The device is in conformity to EN 54-7 standard.

Technical features:

Material	ABS
Power supply	12...28 Vdc
Normal current	50µA a 24 Vdc
Alarm current	25mA a 24 Vdc
LED visibility	360° (double led)
Storage temperature	-10...+70°C
Operating temperature	-10...+70°C
Max. speed air	0,2 m/s
Relative humidity	<93% not-condensing
Index of protection	IP 20
Testing by magnet	Yes
Relay	max. 1A 30Vdc
Signal repeater	14mA a 24 Vdc
Sensor coverage:	40m <sup>2</sup> max
Shielded connection cable	sez. min 0,5 mm <sup>2</sup>
Colour	White



### HEAT DETECTOR

The heat detector has been designed to identify temperatures at which fires may start. When the temperature exceeds the set threshold or when there is a rapid variation in temperature, the relay is activated to signal an alarm.

The device is in conformity to EN 54-5 standard.

Technical features:

Material	ABS
Power supply	12...28 Vdc
Normal current	50µA a 24 Vdc
Alarm current	25mA a 24 Vdc
LED visibility	360° (double LED)
Storage temperature	-10...+70°C
Operating temperature	-10...+70°C
Relative humidity	<93% non-condensing
Index of protection	IP 20
Testing by magnet	Yes
Relay	max. 1A 30Vdc
Signal repeater	14mA a 24 Vdc
Alarm temperature threshold	62°C
Sensor coverage:	40m <sup>2</sup> max
Shielded connection cable	min 0.5 mm <sup>2</sup>
Colour	White

## OPTIONAL ACCESSORIES - CONDENSATE DISCHARGE PUMP



A plastic case contains the vertical type pump, the water tank with float plus safety switch and hydraulic and electric connection.

Together the pump 10 linear meters anti-crushing plastic discharge spiral tube is supplied. The optional must be installed as shown in the documentation delivered together with the unit.

Wiring includes power supply and an alarm, displayed on microprocessor, that includes motor pump thermal protection and tank overflow.


The condensate discharge pump operation is fully automatic.

### WARNING

For all the machines the optional accessory is supplied in mounting kit.

### TECHNICAL DATA

Power supply: 230V~ 50Hz  
 Electrical data: 70W – 0,67A  
 Maximum water flow: 500 l/h  
 Maximum delivery height: 5.0 m  
 Sound level: 45dBA a 1 m  
 Maximum water temperature: 70°C  
 Water acidity: pH>2.5  
 Tray volume: 2.0 l  
 Protection IP 20



## OPTIONAL ACCESSORIES – MODULATING STEAM HUMIDIFIER



Modulating steam humidifier with immersed electrodes fitted with safety and running accessories.

The optional includes the combined temperature / humidity sensor on unit air intake.

The accessory is factory installed and requires water filling connection.

**Humidifier water charge and discharge pipes are not supplied.**

It is recommended to install a filter and a shut-off valve on the pipe to the water inlet.

This humidifier produces non-pressurized steam by electrodes immersed in the water inside the cylinder: they bring the electric phase in the water that works as an electrical resistance and overheats. The steam so produced is distributed with dedicated distributors and used for ambient humidification or for industrial processes.

### CHARACTERISTICS OF THE SUPPLY WATER

The quality of the used water influences the evaporation process, so the humidifier can be fed with **not-treated water, only when potable and non-demineralised.**

### LIMIT VALUES

		Min	Max
Hydrogen ions	pH	7	8,5
Specific conductivity at 20°C	$\sigma_{R, 20^\circ C}$ $\mu S/cm$	300	1250
Total dissolved solids	TDS mg/l	(1)	(1)
Dry residue at 180°C	R <sub>180</sub> mg/l	(1)	(1)
Total hardness	TH mg/l CaCO <sub>3</sub>	100 (2)	400
Temporary hardness	mg/l CaCO <sub>3</sub>	60 (3)	300
Iron + Manganese	mg/l Fe + Mn	0	0,2
Chlorides	ppm Cl	0	30
Silica	mg/l SiO <sub>2</sub>	0	20
Residual chlorine	mg/l Cl <sup>-</sup>	0	0,2
Calcium sulphate	mg/l CaSO <sub>4</sub>	0	100
Metallic impurities	mg/l	0	0
Solvents, diluents, soaps, lubricants	mg/l	0	0

(1) Values depending on specific conductivity; in general: TDS  $\cong$  0,93 \*  $\sigma_{R, 20^\circ C}$ ; R<sub>180</sub>  $\cong$  0,65 \*  $\sigma_{R}$

(2) Not lower than 200% of the chloride content in mg/l di Cl<sup>-</sup>

(3) Not lower than 300% of the chloride content in mg/l di Cl<sup>-</sup>

### WARNING:

- No relation can be demonstrated between water hardness and conductivity.
- **Do not treat water with softeners!** This could cause corrosion of the electrodes or the formation of foam, leading to potential operating problems or failures.
- Do not add disinfectants or corrosion inhibitors to water, as these substances are potentially irritant.
- Is absolutely forbidden to use well water, industrial water or water drawn from cooling circuits; in general, avoid using potentially contaminated water, either from a chemical or bacteriological point of view

### TECHNICAL DATA w-NEXT HD S

MODEL		015	024	041	048	060	072	090	110	122	146
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9
VERSION (1)		U	U	U	U	U	U	U	U	U	U
<b>VAPOUR PRODUCTION</b>	<b>kg/h</b>	<b>3,0</b>	<b>3,0</b>	<b>3,0</b>	<b>3,0</b>	<b>8,0</b>	<b>8,0</b>	<b>8,0</b>	<b>15,0</b>	<b>15,0</b>	<b>15,0</b>
Power input	kW	2,3	2,3	2,3	2,3	6	6	6	11,3	11,3	11,3
Absorbed current (OA)	A	3,2	3,2	3,2	3,2	8,7	8,7	8,7	16,2	16,2	16,2
Max absorbed current (FLA)	A	4,5	4,5	4,5	4,5	12,4	12,4	12,4	23	23	23
Water content	l	3,9	3,9	3,9	3,9	6,4	6,4	6,4	10,3	10,3	10,3
Max water supply pressure	Bar	1÷8	1÷8	1÷8	1÷8	1÷8	1÷8	1÷8	1÷8	1÷8	1÷8
<b>NET WEIGHT (2)</b>	<b>kg</b>	<b>4</b>	<b>4</b>	<b>4</b>	<b>4</b>	<b>10</b>	<b>12</b>	<b>14</b>	<b>16</b>	<b>18</b>	<b>18</b>
<b>HYDRAULIC CONNECTION</b>											
WATER INLET - ISO 228/1 – G M	Ø	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
WATER OUTLET - external diameter	Ø mm	19	19	19	19	19	19	19	19	19	19

1. U = Under, downflow

2. Value to be added to the weight of the standard unit. Does not include the weight of the water content.

# w-NEXT HD S & K

## TECHNICAL DATA w-NEXT HD K

MODEL		015	024	041	048	060	072	090	110	122	146	170
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
<b>VAPOUR PRODUCTION</b>	<b>kg/h</b>	<b>3,0</b>	<b>3,0</b>	<b>3,0</b>	<b>3,0</b>	<b>8,0</b>	<b>8,0</b>	<b>8,0</b>	<b>15,0</b>	<b>15,0</b>	<b>15,0</b>	<b>15,0</b>
Power input	kW	2,3	2,3	2,3	2,3	6,0	6,0	6,0	11,3	11,3	11,3	11,3
Absorbed current (OA)	A	3,2	3,2	3,2	3,2	8,7	8,7	8,7	16,2	16,2	16,2	16,2
Max absorbed current (FLA)	A	4,5	4,5	4,5	4,5	12,4	12,4	12,4	23	23	23	23
Water content	l	3,9	3,9	3,9	3,9	6,4	6,4	6,4	10,3	10,3	10,3	10,3
Max water supply pressure	Bar	1÷8	1÷8	1÷8	1÷8	1÷8	1÷8	1÷8	1÷8	1÷8	1÷8	1÷8
<b>NET WEIGHT (2)</b>	<b>kg</b>	<b>4</b>	<b>4</b>	<b>4</b>	<b>4</b>	<b>10</b>	<b>10</b>	<b>10</b>	<b>18</b>	<b>18</b>	<b>18</b>	<b>18</b>
<b>HYDRAULIC CONNECTION</b>												
WATER INLET - ISO 228/1 – G M	Ø	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
WATER OUTLET - external diameter	Ø mm	19	19	19	19	19	19	19	19	19	19	19

1. U = Under, downflow
2. Value to be added to the weight of the standard unit. Does not include the weight of the water content.

### HUMIDIFIER OVERSIZED

The optional is not available for sizes E1, E2, E3, E7, E8, E9, E10.  
On request it is possible to install the oversized humidifiers.  
The components are the same standard accessory

## TECHNICAL DATA w-NEXT HD S

MODEL		015	024	041	048	060	072	090	110	122	146
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9
VERSION (1)		U	U	U	U	U	U	U	U	U	U
<b>VAPOUR PRODUCTION</b>	<b>kg/h</b>	-	-	-	<b>8,0</b>	<b>15,0</b>	<b>15,0</b>	<b>15,0</b>	-	-	-
Power input	kW	-	-	-	6,0	11,3	11,3	11,3	-	-	-
Absorbed current (OA)	A	-	-	-	8,7	16,2	16,2	16,2	-	-	-
Max absorbed current (FLA)	A	-	-	-	12,4	23	23	23	-	-	-
Water content	l	-	-	-	6,0	10,3	10,3	10,3	-	-	-
Max water supply pressure	Bar	-	-	-	1÷8	1÷8	1÷8	1÷8	-	-	-
<b>NET WEIGHT (2)</b>	<b>kg</b>	-	-	-	<b>10</b>	<b>16</b>	<b>16</b>	<b>16</b>	-	-	-
<b>HYDRAULIC CONNECTION</b>											
WATER INLET - ISO 228/1 – G M	Ø	-	-	-	3/4"	3/4"	3/4"	3/4"	-	-	-
WATER OUTLET - external diameter	Ø mm	-	-	-	19	19	19	19	-	-	-

## TECHNICAL DATA w-NEXT HD K

MODEL		015	024	041	048	060	072	090	110	122	146	170
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
<b>VAPOUR PRODUCTION</b>	<b>kg/h</b>	-	-	-	<b>8,0</b>	<b>15,0</b>	<b>15,0</b>	<b>15,0</b>	-	-	-	-
Power input	kW	-	-	-	6,0	11,3	11,3	11,3	-	-	-	-
Absorbed current (OA)	A	-	-	-	8,7	16,2	16,2	16,2	-	-	-	-
Max absorbed current (FLA)	A	-	-	-	12,4	23	23	23	-	-	-	-
Water content	l	-	-	-	6,0	10,3	10,3	10,3	-	-	-	-
Max water supply pressure	Bar	-	-	-	1÷8	1÷8	1÷8	1÷8	-	-	-	-
<b>NET WEIGHT (2)</b>	<b>kg</b>	-	-	-	<b>10</b>	<b>18</b>	<b>18</b>	<b>18</b>	-	-	-	-
<b>HYDRAULIC CONNECTION</b>												
WATER INLET - ISO 228/1 – G M	Ø	-	-	-	3/4"	3/4"	3/4"	3/4"	-	-	-	-
WATER OUTLET - external diameter	Ø mm	-	-	-	19	19	19	19	-	-	-	-

1. U = Under, downflow
2. Value to be added to the weight of the standard unit. Does not include the weight of the water content.






## OPTIONAL ACCESSORIES – DEHUMIDIFICATION SYSTEM

Components:

- Temperature / Humidity sensor on the air intake.
- Temperature sensor on cooling coil water inlet / outlet.
- Electronic control system of the dew point temperature for the combined intervention of cooling capacity and air flow.

## OPTIONAL ACCESSORIES – 2-WAY BY-PASS VALVE FOR CHILLED WATER CIRCUIT




The optional is not available for size E10.

2-way motorized valve with 0÷10 VDC control actuator and emergency manual control for the third way (by-pass) of the hydraulic circuit.

The valve is in combination with the main 2-way water flow control valve.

The optional accessory is factory installed and don't modify the overall dimensions of the unit.

The coupling to the main 2-way control valve of a second modulating valve, connected in by-pass, allows to obtain the same control system of a 3-way mixing valve for plant with constant water flow. At the same time the appropriate sizing of these valves allows hydraulic balancing of the by-pass way.



### TECHNICAL DATA – 2-WAY VALVE FOR BY-PASS

MODEL	015	024	041	048	060	072	090	110	122	146	170	
SIZE	E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10	
VERSION (1)	U	U	U	U	U	U	U	U	U	U	U	
<b>2-WAY VALVE FOR BY-PASS</b>												
$k_v$ – Flow coefficient	m <sup>3</sup> /h	6,3	6,3	8,6	8,6	8,6	16,0	25,0	25,0	25,0	40,0	40,0

1. U = Under, downflow

### **IMPORTANT**

For further information, please refer to chapter “VALVE PRESSURE DROP CALCULATION AS FUNCTION OF WATER FLOW RATE”



## OPTIONAL ACCESSORIES – ELECTRIC HEATERS



Electric heater consisting of finned aluminum elements, ensuring low surface temperature and deleting the air ionization problems. The optional is installed downstream the main cooling coil.

In electric heaters with three working steps the activation is binary type.

Components:

- Electric heater in aluminium armoured elements with integral fins
- Electrical control
- Safety thermostat.

### TECHNICAL DATA w-NEXT HD S

MODEL		015	024	041	048	060	072	090	110	122	146
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9
VERSION (1)		U	U	U	U	U	U	U	U	U	U
THERMAL CAPACITY	kW	5,1	5,1	6,0	6,0	9,0	13,5	13,5	13,5	18,0	18,0
Absorbed current (OA)	A	7,3	7,3	8,6	8,6	12,9	19,4	19,4	19,4	25,9	25,9
First working step	kW	5,1	5,1	3,0	3,0	3,0	4,5	4,5	4,5	4,5	4,5
Second working step	kW	-	-	3,0+3,0	3,0+3,0	6,0	9,0	9,0	9,0	13,5	13,5
Third working step	kW	-	-	-	-	3,0+6,0	4,5+9,0	4,5+9,0	4,5+9,0	4,5+13,5	4,5+13,5
NET WEIGHT (2)	kg	4	4	7	7	9,5	10	9,5	9,5	11	11

### TECHNICAL DATA w-NEXT HD K

MODEL		015	024	041	048	060	072	090	110	122	146	170
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
THERMAL CAPACITY	kW	5,1	5,1	6,0	6,0	9,0	13,5	13,5	13,5	18,0	18,0	27,0
Absorbed current (OA)	A	7,4	7,4	8,7	8,7	13,0	19,5	19,5	19,5	26,0	26,0	39,0
First working step	kW	5,1	5,1	3,0	3,0	3,0	4,5	4,5	4,5	4,5	4,5	9,0
Second working step	kW	-	-	3,0+3,0	3,0+3,0	6,0	9,0	9,0	9,0	13,5	13,5	18,0
Third working step	kW	-	-	-	-	3,0+6,0	4,5+9,0	4,5+9,0	4,5+9,0	4,5+13,5	4,5+13,5	9,0+18,0
NET WEIGHT (2)	kg	4	4	7	7	9,5	10	9,5	9,5	11	11	15

1. U = Under, downflow
2. Value to be added to the weight of the standard unit.

## OVERSIZED ELECTRIC HEATERS

On request it is possible to install the oversized electric heating system.  
The components are the same standard accessory

### TECHNICAL DATA w-NEXT HD S


MODEL		015	024	041	048	060	072	090	110	122	146
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9
VERSION (1)		U	U	U	U	U	U	U	U	U	U
<b>THERMAL CAPACITY</b>	<b>Kw</b>	--	--	9,0	9,0	13,5	18,0	18,0	18,0	27,0	27,0
Absorbed current (OA)	A	--	--	12,9	12,9	19,5	26,0	26,0	26,0	39,0	39,0
First working step	kW	--	--	4,5	4,5	4,5	4,5	4,5	4,5	9,0	9,0
Second working step	kW	--	--	4,5+4,5	4,5+4,5	9,0	13,5	13,5	13,5	18,0	18,0
Third working step	kW	--	--	--	--	4,5+9,0	4,5+13,5	4,5+13,5	4,5+13,5	9,0+18,0	9,0+18,0
<b>NET WEIGHT (2)</b>	<b>kg</b>	--	--	7	7	9,5	12	11,5	11,5	14,5	14,5

### TECHNICAL DATA w-NEXT HD K

MODEL		015	024	041	048	060	072	090	110	122	146	170
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
<b>THERMAL CAPACITY</b>	<b>kW</b>	--	--	9,0	9,0	13,5	18,0	18,0	18,0	27,0	27,0	36,0
Absorbed current (OA)	A	--	--	12,9	12,9	19,5	26,0	26,0	26,0	39,0	39,0	52
First working step	kW	--	--	4,5	4,5	4,5	4,5	4,5	4,5	9,0	9,0	13,5
Second working step	kW	--	--	4,5+4,5	4,5+4,5	9,0	13,5	13,5	13,5	18,0	18,0	22,5
Third working step	kW	--	--	--	--	4,5+9,0	4,5+13,5	4,5+13,5	4,5+13,5	9,0+18,0	9,0+18,0	13,5+22,5
<b>NET WEIGHT (2)</b>	<b>kg</b>	--	--	7	7	9,5	12	11,5	11,5	14,5	14,5	18,5



1. U = Under, downflow
2. Value to be added to the weight of the standard unit.

## OPTIONAL ACCESSORIES - FLOOR STAND





The accessory is supplied as an assembly kit  
 It is not possible to match the unit floor stand with plenum installed under the machine.  
 For a correct installation of the air conditioner we suggest you to utilize a gasket between the floor stand and the unit base.  
 The floor stand is available in 3 different heights.



**SIZE E1 – E2 – E3 – E3P**





**SIZE E4 – E5**



**SIZE E6 – E7 - E8 – E9**



**SIZE E10**



SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
A	mm	650	785	1085	1085	1305	1630	1873	2175	2499	2899	3510
B	mm	650	650	750	905	905	905	905	905	905	905	905
C	mm	524	659	959	959	955	1280	761,5	912,5	1074,5	1274,5	1053
D	mm	691	691	791	946	945	945	945	945	945	945	945

MODEL		Hmax350	Hmax450	Hmax510
H min height	mm	255	355	400
H max height	mm	350	450	510

## OPTIONAL ACCESSORIES - DOUBLE PANELS IN EUROCLASS A1

The optional is designed to supply the panels only in Euroclass A1 of reaction to fire, furthermore allows a noise insulation of the panels of the air conditioners.

The pressure level reduction of the unit is about 2 dB(A). The reduction refers ONLY to the sound level radiated from the unit or in front of the unit. The noise level data on return and delivery air do not undergo reductions.

The accessory includes:

- External part as standard panel.
- Internal part in galvanized steel sheet.
- The inside noise insulation with special soundproof material.

### REACTION TO FIRE CLASSIFICATION

On Italian territory, the classification is per the D.M. of June 26, 1984 and subsequent amendments, providing for a sort in "Classes" from 0 (non-combustible material) to 5 (extremely flammable material). In Europe, the classification is regulated per UNI EN 13501-1: 2009 ordered to "Euro-classes", from A1 (non-combustible material) to F (highly flammable material).

A comparison of the Italian and European classes is not possible because the methods and evaluation criteria are completely different. The comparison table below is being considered purely indicative.

Definition	Italian classes	Euro-classes
Non-combustible material	Class 0	A1
Combustible material, very limited contribution to fire	Class 1	A2 – B
Combustible material, limited contribution to fire	Class 2	A2 – B - C
Combustible material, medium contribution to fire	Class 3	C – D
Combustible material, highly contribution to fire	Class 4	E
Combustible material, easily flammable	Class 5	F

Is possible to provide the sandwich panels for the OVER units with air flow from the top. This implies that the air intake must necessarily be from the base of the unit with front blind paneling.

The accessory increases the unit weight:

SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
Weight increasing (2)	kg	30	48	55	65	70	86	110	130	145	165	195

1. U = Under, downflow
2. Add this value to the total unit weight

## OPTIONAL ACCESSORIES – ePM<sub>10</sub> 50% EFFICIENCY AIR FILTERS

The ePM<sub>10</sub> 50% air filters (according to ISO EN 16890), replace the standard one. The filters generate a pressure drops higher than the standard ones. The filters are made of glass micro-fibre and are not regenerable.

### w-NEXT HD S

MODEL		015	024	041	048	060	072	090	110	122	146
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9
VERSION (1)		U	U	U	U	U	U	U	U	U	U
Additional pressure drops (2)	Pa	71	125	115	89	73	69	77	79	71	71


### w-NEXT HD K

MODEL		015	024	041	048	060	072	090	110	122	146	170
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
Additional pressure drops (2)	Pa	67	122	115	89	73	69	76	78	70	72	71

1. U = Under, downflow
2. Additional pressure drops referred to nominal air flow and clean filter.



## OPTIONAL ACCESSORIES – NON- RETURN MOTORIZED DAMPER




Accessory installed on units air return and it can be matched to plenums and floor stand.

### FRAMEWORK

- Frame in galvanized steel sheet with protective surfaces treatment in compliance with UNI ISO 9227/ASTMB117 and ISO 7253, and painted with epoxy powders. Colour RAL 9005;
- Opposed blade dampers in galvanized steel sheet.
- Actuator for damper control.
- Terminals for electric connection to the unit.


For a correct installation, we suggest you to utilize a gasket between the damper and the unit or the plenum or the floor stand.



SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
A	mm	650	785	1085	1085	1305	1630	1873	2175	2499	2899	3510
B	mm	650	650	750	905	905	905	905	905	905	905	905
C	mm	300	450	750	750	900	1250	1500	1750	2000	2300	2800
D	mm	510	510	610	710	710	710	710	710	710	710	710
E	mm	231	216	216	216	142	204	250,5	226,5	238,5	288,5	294
F	mm	73	73	73	73	202	115	61,5	137,5	199,5	249,5	355
G	mm	46	46	46	46	61	61	61	61	61	61	61
H	mm	170	170	170	170	170	170	170	170	170	170	170
Weight (2)	kg	20	23	30	35	40	50	58	65	75	90	115

1. U = Under, downflow
2. Add this value to the total unit weight

## INSTALLATION EXAMPLE








### WORKING LOGIC

The damper opens at supply fans activation to allow air flow.

When the fans stop for failure or stop command, the damper closes, preventing air flow into the unit.

### OPTIONAL ACCESSORIES - PLENUM ON AIR DELIVERY/RETURN



The optional is supplied separately and the installation on the unit is at Customer care.  
The plenums can be used for version Under, both on supply and return air.  
The plenums have same technical characteristics and dimensions of the machine cabinet.

**It is possible to install only a single plenum to ensure stability to the unit.**

#### FRAMEWORK

- Frame in aluminium extrusion, painted with epoxy powders. Colour RAL 9005;
- Panels in galvanized steel sheet with protective surfaces treatment in compliance with UNI ISO 9227/ASTMB117 and ISO 7253, and painted with epoxy powders. Colour RAL 9005;
- Panels insulated with polyurethane foam and seals to ensure air tight.
- Panels fixed with screws.
- Removable panels.
- Set of fixing elements to fasten the plenum to the unit.

#### Type of plenum:

- Empty plenum. Available in Euroclass A1.
- Plenum with noise absorption partitions
- Plenum with high efficiency filters.
- Plenum with frontal grille. Available in Euroclass A1.
- Plenum with frontal and lateral grilles. Available in Euroclass A1.
- Plenum with frontal grille and noise absorption partitions


#### **WARNING**

**In UNDER version units the hydraulic piping is inside the machine.**

**The air delivery plenums sometime don't allow the extension of the pipes downwards.**


**In special cases, to keep the connections inside the machine, foresee a plenum 200mm higher than the standard one.**





## EMPTY PLENUM

The plenum is void and can be used to rise the return air inlet/outlet.  
Remove the frontal panels for inspection.




SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
A	mm	490	490	490	510	510	510	510	510	510	510	510
Weight (2)	kg	20	21	20	25	30	40	45	50	60	70	78

## EMPTY PLENUM REACTION TO FIRE – EUROCLASS A1


SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
A	mm	490	490	490	510	510	510	510	510	510	510	510
Weight (2)	kg	25	27	27	33	39	50	56	62	74	85	96

1. U = Under, downflow
2. Add this value to the total unit weight



## PLENUM ON AIR DELIVERY WITH NOISE ABSORPTION PARTITIONS

The plenum is fitted with noise absorption partitions to reduce the noise emission.  
Remove the frontal panels for inspection.



SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
A	mm	490	490	490	510	510	510	510	510	510	510	510
Weight (2)	kg	25	27	30	36	45	50	65	80	90	100	120

1. U = Under, downflow
2. Add this value to the total unit weight


### w-NEXT HD S

MODEL		015	024	041	048	060	072	090	110	122	146	
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	
<b>NOISE LEVEL (1)</b>												
On air delivery Under	dB(A)	63,2	71,5	73,4	74,0	75,5	76,1	76,4	76,8	78,9	78,7	
On air intake Under	dB(A)	57,0	61,8	63,4	65,6	67,1	66,2	68,0	68,4	69,0	70,3	
On front side Under	dB(A)	47,7	52,3	53,9	56,1	57,6	56,6	58,6	59,0	59,4	60,9	
Additional pressure drops (2)	Pa	31	62	54	58	69	67	76	81	71	75	
Air flow	m <sup>3</sup> /h	3100	5300	8300	10500	13400	16800	20500	24300	26500	31500	

### w-NEXT HD K


MODEL		015	024	041	048	060	072	090	110	122	146	170
SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
<b>NOISE LEVEL (1)</b>												
On air delivery Under	dB(A)	63,2	70,8	72,8	74,0	75,2	76,1	76,4	77,0	78,9	78,7	78,8
On air intake Under	dB(A)	57,1	61,0	62,9	65,6	66,8	66,2	68,0	68,6	69,0	70,3	70,4
On front side Under	dB(A)	47,8	51,6	53,3	56,1	57,4	56,6	58,6	59,1	59,4	60,9	60,9
Additional pressure drops (2)	Pa	28	45	50	57	68	64	73	79	71	75	112
Air flow	m <sup>3</sup> /h	3100	5100	8300	10500	13200	16800	20500	24300	26500	31500	36000

1. Noise pressure level at 1 meter in free field – ISO 3744
2. Value to be subtracted from the nominal external static pressure of the unit.



## PLENUM ON AIR DELIVERY WITH HIGH EFFICIENCY FILTERS

The plenum must be installed on air delivery.  
 The plenum is fitted with high efficiency rigid bag filters.  
 Filters are made of glass micro fibre and are not regenerable.  
 Remove the frontal panels for filters replacement.



SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
A	m	490	490	490	510	510	510	510	510	510	510	510
Weight (2)	kg	26	27	30	33	45	55	65	80	90	100	120


### w-NEXT HD S

SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9
VERSION (1)		U	U	U	U	U	U	U	U	U	U
<b>PRESSURE DROPS (3)</b>											
Filters ePM <sub>2.5</sub> 50%	Pa	85	171	172	146	148	161	195	167	141	167
Filters ePM <sub>1</sub> 50%	Pa	105	209	211	178	181	197	239	204	173	204
Filters ePM <sub>1</sub> 85%	Pa	126	254	256	216	220	239	289	248	209	248

### w-NEXT HD K

SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
<b>PRESSURE DROPS (3)</b>												
Filters ePM <sub>2.5</sub> 50%	Pa	80	167	172	145	148	161	194	166	140	167	114
Filters ePM <sub>1</sub> 50%	Pa	98	205	211	178	181	197	237	203	172	204	161
Filters ePM <sub>1</sub> 85%	Pa	119	249	256	215	220	239	289	247	208	248	195


1. U = Under, downflow
2. Add this value to the total unit weight
3. Data referred to the nominal air flow and clean filters. Value to be subtracted from the nominal external static pressure of the unit.



## PLENUM ON AIR DELIVERY WITH FRONTAL GRILLE

The plenum allows the frontal air distribution directly into the room.

The plenum is supplied with air distribution grille with double row adjustable grilles on front side.



SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
A	mm	490	490	490	510	510	510	510	510	510	510	510
Weight (2)	kg	23	26	28	34	39	50	65	75	90	110	130

## PLENUM ON AIR DELIVERY WITH FRONTAL GRILLE REACTION TO FIRE – EUROCLASS A1



SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
A	mm	490	490	490	510	510	510	510	510	510	510	510
Weight (2)	kg	29	32	36	44	50	63	79	91	108	130	153

1. U = Under, downflow
2. Add this value to the total unit weight

## PLENUM ON AIR DELIVERY WITH FRONTAL AND LATERAL GRILLES

The plenum allows the air distribution directly into the room.

The plenum is supplied with air distribution grilles with double row adjustable grilles on front and lateral side.





SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
A	mm	490	490	490	510	510	510	510	510	510	510	510
Weight (2)	kg	21	23	30	36	45	50	65	75	90	100	120

## PLENUM ON AIR DELIVERY WITH FRONTAL AND LATERAL GRILLES REACTION TO FIRE – EUROCLASS A1

SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
A	mm	490	490	490	510	510	510	510	510	510	510	510
Weight (2)	kg	25	28	37	44	54	61	77	89	106	118	142

1. U = Under, downflow
2. Add this value to the total unit weight

## OPTIONAL ACCESSORIES – DIRECT FREE-COOLING PLENUM



The optional is supplied separately and the installation on the unit is at Customer care.  
The plenums have same technical characteristics and base dimensions of the machine cabinet.  
The optional allow to obtain free-cooling by direct ambient air intake into the room.  
The dampers are proportionally managed by the microprocessor control, that regulates the quantity of the ambient air to put in the room according to the set-point.

### COMPONENTS


- Frame in aluminium extrusion, painted with epoxy powders. Colour RAL 9005;
- Panels in galvanized steel sheet with protective surfaces treatment in compliance with UNI ISO 9227/ASTMB117 and ISO 7253, and painted with epoxy powders. Colour RAL 9005;
- Panels insulated with polyurethane foam and seals to ensure air tight.
- Panels fixed with screws.
- Removable panels.
- Opposed blade dampers in galvanized steel sheet and safety grille for ambient air and room air suction.
- Actuator for each damper.
- Terminals for electric connection to the unit.
- Combined Temperature / Humidity sensor on machine air suction. The sensor must be moved outside the air conditioners for a proper read of the room temperature value.
- Temperature sensor for outdoor air. The sensor must be installed in the outdoor air suction duct or anyway protected against atmospheric agent.
- Free contact for free-cooling operating status monitoring.
- Set of fixing elements to fasten the plenum to the unit.

For a correct installation use a gasket between the plenum and the unit.

### **WARNING**

**IT IS COMPULSORY TO INSTALL INTO THE ROOM AN APPROPRIATELY SIZED OVERPRESSURE DAMPER TO ALLOW THE ROOM AIR EXHAUSTION DURING FREE-COOLING WORKING MODE.**



### INSTALLATION EXAMPLE





Ducting are at Customer care.  
We suggest you to install a rain-proof grille on ambient air intake.

## UNDER VERSION



### SIZE E1 / E2 / E3 / E3P



### SIZE E4 / E5



### SIZE E6 / E7 / E8 / E9 / E10



SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
VERSION (1)		U	U	U	U	U	U	U	U	U	U	U
A	mm	650	785	1085	1085	1305	1630	1873	2175	2499	2899	3510
B	mm	490	490	490	630	630	630	630	630	630	630	630
C	mm	650	650	750	905	905	905	905	905	905	905	905
D	mm	30	30	30	40	40	40	40	40	40	40	40
E	mm	430	430	430	550	550	550	550	550	550	550	550
F	mm	590	725	1025	1005	1035	1335	1664	1965	2220	2670	3135
G	mm	--	--	--	--	135	147,5	209	210	279	229	375
H	mm	--	--	--	275	275	275	275	275	275	275	275
Weight (2)	kg	24	27	35	43	53	61	78	90	110	130	155

1. U = Under, downflow
2. Add this value to the total unit weight

### OPTIONAL ACCESSORIES – COOLNET



**COOLNET:** Intelligent NET for IT Cooling that maximizes the energy saving in LOAD SHARING

#### MAIN FEATURES

COOLNET is a software that applies to chilled water air conditioners microprocessor control system. It optimizes the LOAD SHARING working mode and maximizes the energy savings.

### OPTIONAL ACCESSORIES – ADAPTIVE SET-POINT



#### ADAPTIVE SET-POINT

An advanced algorithm that instantaneously detects the real thermal load of the indoor units and then conveys this information to the outdoor chillers, strongly increasing their operation.

- Dynamic variation of the chillers set point and water flow.
- Increasing of the free cooling mode.
- Adoption of the active redundancy system to better exploit stand-by chillers.

#### DATA CENTER MANAGER (Optional accessory)

DATA CENTER MANAGER is a centralized management system that ensures a smart communication between indoor chilled water units and the outdoor chillers.

The device manages the outdoor units according to the inlet and outlet temperature registered by the probes and by request of the indoor unit.

### OPTIONAL ACCESSORIES – KIPlink – Keyboard in your Pocket



**KIPlink** - Keyboard In Your Pocket - is the innovative user interface based on WiFi technology that allows one to operate on the unit directly from the smartphone or tablet. Using KIPlink, it is possible to turn the unit on and off, adjust the set-point, plot the main operating variables, monitor in detail the status of the refrigerant circuits, the compressors, the fans and display and reset the possible alarms.

Scan the QR code on the electrical board of the unit to have access to the unit control through web browser web or App. The access is possible within the local WiFi network.

KIPlink hardware:


- Wi-Fi antenna in the electrical board;
- ON/OFF button with power LED and Unit status LED. Provided when the unit is equipped with KIPlink and without 6-keys keyboard (optional).

KIPlink allows;

- Easy and enhanced unit management
- Real-Time graphs and key trends
- Different information for each kind of user



## OPTIONAL ACCESSORIES – CLOUD PLATFORM: WEB SERVICES BASED ON CLOUD TECHNOLOGY FOR REMOTE MONITORING AND MANAGEMENT OF AIR CONDITIONING PLANTS.



**CLOUD PLATFORM** is an ecosystem of web services for remote monitoring and management of air conditioning plants; specifically designed for mobile usage on tablets and smartphones, it allows to access plant data everywhere on the go so saving time, money and delivering a higher service level to the customer.

### TECHNOLOGY

Based on cloud technology it allows, through machines data telemetry, to monitor and control units on the field, process data and perform proactive maintenance.

The hardware heart of the system is the Cloud box that can collect plant data (up to 31 devices and up to 1000 registers).

Connectivity between monitored devices and Cloud box may be wired in Ethernet, RS485, RS232 and must be in MODBUS protocol.

Cloud Platform then send these data to dedicated server in cloud in through the mobile (GPRS or 3G) network or ADSL.

Information security; each communication channel can be encrypted in VPN, ensuring data privacy.

### USER SIDE

Cloud Platform is designed for mobile communication. So, the user just need a tablet or a smartphone to access the RC Cloud Platform and check his plant.

Cloud Platform App is available both on Android and iOS operating systems so the environment may be accessed directly from them beyond company site and platform site. Access through pc is available too.

### FUNCTIONS

#### Telemetry & Data Export

Data polling and history of all data (1 year).  
Export diagram and table (csv). **Your data always on the go.**

#### Multi Device

Many type of devices can be connected to the same box (chillers, close control, energy meters, flow meters, pumps,...).  
Only a request: MODBUS protocol. Electrical connection in Ethernet, RS 485 or RS 232.

#### Multi Language

English native, Cloud Platform language pack is available for the main markets.

#### Virtual Display

Monitoring and control (on/off, alerts reset, main parameters change) as being beside the unit, in an augmented reality way.

Designed for Mobile.

**Same as standing in front of the unit, when in your office or in any other place.**

#### Internet Connectivity

ETHERNET + GPRS + 3G connection capability on Public and Virtual Private Network (VPN).

#### Alerts Warning through:


- Push notification
- e-mail
- Voice calls
- SMS

#### Processing of specialized plant KPI to get:

- Energy performance (gross instant EER)
- Components Failure Forecast (coming soon)
- Unit diagnosis

## MACHINE DRAWINGS



Dimensions in mm - UNDER E1, E2




MODELLO / MODEL	A	DIAMETRO CONNESSIONI / CONNECTION DIAMETERS
w-NEXT HD S / K E1	650	R 1"
w-NEXT HD S / K E2	785	R 1 1/4"

\* CON SERRANDA DI NON RITORNO  
ALTEZZA TOTALE = 2095

\* WITH NON RETURN MOTORIZED DAMPER  
TOTAL HEIGHT = 2095





CONNESSIONI / CONNECTIONS	
9 USCITA' ACQUA REFRIGERATA	CHILLED WATER OUTLET
8 INGRESSO ACQUA REFRIGERATA	CHILLED WATER INLET
5 ALIMENTAZIONE ELETTRICA	POWER SUPPLY
4 CARICO ACQUA UMIDIFICATORE G 3/4"	HUMIDIFIER FILL G 3/4"
SCARICO ACQUA UMIDIFICATORE Ø 19mm	HUMIDIFIER DRAIN Ø 19mm
3 SCARICO CONDENSATA Ø 19mm	CONDENSATE DISCHARGE Ø 19mm




MODELLO / MODEL	A	B	C	D	E	F	G	DIAMETRO, CONNESSIONI CONNECTION DIAMETERS
w-NEXT HD S / K E3	1085	1925	750	775	45	160	75	R 1 1/2"
w-NEXT HD S / K E3P	1085	1925	905	930	45	280	120	R 1 1/2"
w-NEXT HD S / K E4	1305	1980	905	930	60	275	120	R 2"

- \* CON SERRANDA DI NON RITORNO  
ALTEZZA TOTALE = B+170
- \* WITH NON RETURN MOTORIZED DAMPER  
TOTAL HEIGHT = B+170





CONNESSIONI / CONNECTIONS	
9	USCITA ACQUA REFRIGERATA CHILLED WATER OUTLET
8	INGRESSO ACQUA REFRIGERATA CHILLED WATER INLET
5	ALIMENTAZIONE ELETTRICA POWER SUPPLY
4	CARICO ACQUA UMIDIFICATORE G 3/4" HUMIDIFIER FILL G 3/4" SCARICO ACQUA UMIDIFICATORE Ø 19mm HUMIDIFIER DRAIN Ø 19mm
3	SCARICO CONDENSATA Ø 19mm CONDENSATE DISCHARGE Ø 19mm




MODELLO / MODEL	A	DIAMETRO CONNESSIONI / CONNECTION DIAMETERS
w-NEXT HD S / K E5	1630	R 2"
w-NEXT HD S / K E6	1673	R 2" 1/2

- \* CON SERRANDA DI NON RITORNO  
ALTEZZA TOTALE = 2150
- \* WITH NON RETURN MOTORIZED DAMPER  
TOTAL HEIGHT = 2150




DIAMETRO CONNESSIONI / DIAMETER CONNECTIONS	
9	URTO ACQUA REFRIGERANTE / CHILLED WATER INLET
8	INFESSIONE ACQUA REFRIGERANTE / CHILLED WATER OUTLET
5	ALIMENTAZIONE ELETTRICA / POWER SUPPLY
4	CARICO ACQUA UMIDIFICATORE Ø 3/4" / HUMIDIFIER FILL Ø 3/4"
3	SCARICO ACQUA UMIDIFICATORE Ø 19mm / HUMIDIFIER DRAIN Ø 19mm
3	SCARICO VASCA CONDENSATA Ø 19mm / CONDENSATE DISCHARGE Ø 19mm




MODELLO / MODEL	A	B	C	D	DIAMETRO CONNESSIONI / CONNECTION DIAMETERS
w-NEXT HD S / K E7	2175	SOLO PER E7 ONLY FOR E7	SOLO PER E7/E8 ONLY FOR E7/E8	250	R 2" 1/2
w-NEXT HD S / K E8	2489	-	-	250	R 3"
w-NEXT HD S / K E9	2889	130	170	-	R 3"

\* CON SERRANDA DI NON RITORNO  
ALTEZZA TOTALE = 2150

\* WITH NON RETURN MOTORIZED DAMPER  
TOTAL HEIGHT = 2150



DIAMETRI CONNESSIONI / DIAMETER CONNECTIONS	
9	USCITA ACQUA REFRIGERANTE / CHILLED WATER OUTLET
8	INGRESSO ACQUA REFRIGERANTE / CHILLED WATER INLET
5	ALIMENTAZIONE ELETTRICA / POWER SUPPLY
4	CARICO ACQUA UMIDIFICATORE G. 3/4" / HUMIDIFIER FILL G. 3/4"
3	SCARICO ACQUA UMIDIFICATORE Ø 18mm / HUMIDIFIER DRAIN Ø 18mm
3	SCARICO VASCA CONDENSATA Ø 18mm / CONDENSATE DISCHARGE Ø 18mm




MODELLO / MODEL	DIAMETRO CONNESSIONI / CONNECTION DIAMETERS
w-NEXT HD K E10	DN80 FLANGE CONN.

\* CON SEPARANDA DI NON RITORNO  
ALTEZZA TOTALE = 2150


\* WITH NON RETURN MOTORIZED DAMPER  
TOTAL HEIGHT = 2150

DIAMETRI CONNESSIONI / DIAMETER CONNECTIONS	
9 USCITA ACQUA REFRIGERATA / CHILLED WATER OUTLET	CHILLED WATER OUTLET
8 INGRESSO ACQUA REFRIGERATA / CHILLED WATER INLET	CHILLED WATER INLET
5 ALIMENTAZIONE ELETTRICA / POWER SUPPLY	POWER SUPPLY
4 CARICO ACQUA UMIDIFICATORE Ø 34" / HUMIDIFIER FILL Ø 34"	HUMIDIFIER FILL Ø 34"
3 SCARICO VASCA CONDENSATI Ø 19mm / CONDENSATE DISCHARGE Ø 19mm	CONDENSATE DISCHARGE Ø 19mm



## HOLE IN THE RAISED FLOOR FOR DOWNFLOW VERSION


### HOLE IN THE RAISED FLOOR WITHOUT FLOOR STAND



Foresee a hole in the floor with the following dimensions:

SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
a	mm	95	95	95	95	110	110	110	110	110	110	110
b	mm	560	560	660	815	785	785	785	785	785	785	785
c	mm	560	695	995	995	1185	1510	1755	2055	2380	2780	3390

### HOLE IN THE RAISED FLOOR WITH FLOOR STAND (OPTION)




Foresee a hole in the floor with the following dimensions:

SIZE		E1	E2	E3	E3P	E4	E5	E6	E7	E8	E9	E10
a	mm	50	50	50	50	50	50	50	50	50	50	50
b	mm	670	670	770	925	925	925	925	925	925	925	925
c	mm	670	805	1105	1105	1325	1650	1895	2195	2520	2920	3530


## EXAMPLE FOR MACHINES NOISE EMISSION CALCULATION

### UNDER MACHINE WITH DUCT ON AIR INTAKE



- Lp A = Front side Under catalogue value
- Lp B = Air delivery Under catalogue value
- Lp C = Air intake Under catalogue value
- The points B and C do not influence the point A


### UNDER MACHINE WITH PLENUM ON AIR DELIVERY



- Lp A = Front side Under catalogue value
- Lp B = Air delivery Under catalogue value – plenum noise reduction
- Lp C = Air intake Under catalogue value
- $Lp A+C = 10 \log_{10} \left( 10^{\frac{LpA}{10}} + 10^{\frac{LpC}{10}} \right)$

The point B do not influence the point A

### UNDER MACHINE WITH PLENUM ON AIR INTAKE



- Lp A = Front side Under catalogue value
- Lp B = Air delivery Under catalogue value
- Lp C = Air intake Under catalogue value – plenum noise reduction
- $Lp A+C = 10 \log_{10} \left( 10^{\frac{LpA}{10}} + 10^{\frac{LpC}{10}} \right)$

The point B do not influence the point A

### EXAMPLE FOR MACHINES NOISE EMISSION CALCULATION

The noise pressure level of an installed unit is affected by the room acoustic characteristics.  
Please consider an average noise increase of +4/+6 dB(A).



### VALVE PRESSURE DROP CALCULATION AS FUNCTION OF WATER FLOW RATE

Flow coefficient  $k_v$  defines the water flow (between 5°C and 40°C) expressed in m<sup>3</sup>/h that cross a valve with a pressure drop of 1bar (100kPa).

With this data is possible to calculate the localized pressure drop as function of the water flow rate.

$$\Delta P = (Q / k_v)^2$$

$\Delta P$  (bar) = localized pressure drop of valve;

$Q$  (m<sup>3</sup>/h) = water flow rate – it varies according to the desired operating condition;

$k_v$  (m<sup>3</sup>/h) = valve flow coefficient.

The formula allows to calculate the value of the localized pressure drop (in bar).

The pressure drops values showed on the documentation are supplied in kPa.

Is possible to change from one unit to another through the following conversion.

$$1 \text{ bar} = 100\text{kPa}$$

### CALCULATION EXAMPLE OF 2-WAY VALVE FOR BY-PASS PRESSURE DROP IN FUNCTION OF CHILLED WATER COIL WATER FLOW RATE

#### w-NEXT HD S 146 E9 – CHILLED WATER COIL

Example at nominal conditions. Characteristics referred to entering air at 24°C-50%RH with chilled water temperature 7-12°C - 0% glycol.

Water flow rate: 24,9 m<sup>3</sup>/h

Valve flow coefficient  $k_v$ : 40 m<sup>3</sup>/h

$$\text{2-way valve for by-pass pressure drop: } \Delta P = (Q / k_v)^2 = (29,4 / 40)^2 = 0,387 \text{ (bar)} * 100 \text{ (kPa / bar)} = 38,7 \text{ kPa}$$



for a greener tomorrow

Eco Changes is the Mitsubishi Electric Group's environmental statement, and expresses the Group's stance on environmental management. Through a wide range of businesses, we are helping contribute to the realization of a sustainable society.



## MITSUBISHI ELECTRIC HYDRONICS & IT COOLING SYSTEMS S.p.A.

Via Caduti di Cefalonia, 1 - 36061 Bassano del Grappa (VI) Italy  
Ph. (+39) 0424 509 500 • Fax (+39) 0424 509 509  
[www.melcohit.com](http://www.melcohit.com)