

Unit description



Outdoor unit for the production of chilled water, equipped with oil-free centrifugal compressors, R513A refrigerant, axial EC fans, condensing coil with copper tubes and aluminum fins, shell and tube flooded evaporator and electronic expansion valve. Base, supporting structure and panels are of galvanized epoxy powder coated steel. The unit is supplied with refrigerant and has been factory tested. In free cooling mode, the liquid is cooled by outdoor air, thus lowering the load of the compressors until it is reduced to zero. The NG configuration complies with applications where it is not allowed or desired the use of ethylene glycol.

Versions

- **K** - Key efficiency, compact version
- **CA** - High energy efficiency units

Configurations

- - - Basic function
- **NG** - Function for free-cooling without use of glycole

Features

- **ENERGY SAVING**
Energy saving guaranteed by free-cooling, which exploits the low external air temperatures; free-cooling control with optional modulating valve.
- **VERY HIGH EFFICIENCY**
Top-level seasonal efficiency thanks to technological solutions at the forefront: magnetic levitation centrifugal compressors, flooded evaporator, EC fans and advanced control algorithms.
- **WIDE RANGE**
Extended capacity range.

- **LOW INRUSH CURRENTS**
Reduced breakaway starting currents thanks to the revolutionary centrifugal compressor.
- **EXTREMELY SILENT OPERATION**
Extremely silent operation in line with the best on the market, and highly reduced vibrations
- **INTEGRATED HYDRONIC GROUP**
It consists of 2 pumps with 4-pole motor, fixed or variable speed, with high or low head options to satisfy the different installation requirements.

Accessories

- Modulating valve for water temperature control in Free-Cooling mode
- Hydronic group
- VPF (Variable Primary Flow) kit: variable flow pumps with on board regulation
- Compressor power factor correction
- Set-up for remote connectivity with ModBus/Echelon protocol cards
- Touch Screen visual display
- Remote control keyboard (distance to 200m and to 500m)