

Unit description



Outdoor unit for the production of chilled water with hermetic rotary Scroll compressors, ozone-friendly refrigerant R410A, axial-flow fans, braze-welded plate-type heat exchanger, micro-channel full-aluminum air coils and thermostatic expansion valve. The range is composed by units equipped with four compressors in tandem configuration on two independent refrigeration circuits.

Versions

- **K** - Key efficiency, compact version
- **LN-K** - Low Noise, Key efficiency and compact version
- **SL-K** - Super Low noise, Key efficiency and compact version

Configurations

- - - Basic function
- **D** - Partial condensing heat recovery function

Features

- **MAXIMUM COMPACTNESS**
This new range is available in the K version, that integrates the maximum compactness with a qualifying unit's efficiency. This allow to achieve a very high flexibility in the design process as well as during the on-site installation operations, offering a premium solution in case of reduced clearances or when retrofitting existing installations.
- **ALUMINIUM MICRO-CHANNEL HEAT EXCHANGERS**
The full aluminium micro-channel condenser coils deliver high efficiency whilst ensuring a reduced refrigerant volume and a lower unit weight. The e-coating protection (optional) grants the highest level of resistance to corrosion in any condition, even in the most aggressive environments.
- **WIDE OPERATING RANGE**
Full load operation is ensured with outdoor air temperature up to 46°C, partial load operation is possible up to or even beyond 50°C. The unit can

produce chilled water at negative temperature (down to -10°C of leaving water temperature). Dedicated accessories allow the unit operation down to -20°C of outdoor air temperature.

- **INTEGRATED HYDRONIC GROUP**
The optional built-in hydronic module already contains the main water circuit components; it is available with single or twin in-line, for achieving both low or high head.

Accessories

- Microchannel coils with e-coating protection
- Traditional coils with copper tubes and aluminium fins, also available with prepainted fins or Fin Guard Silver protective treatment.
- Copper-Copper heat exchanger coils
- Electronic expansion valve
- Compressor power factor correction
- Soft start
- Compressor suction and discharge valves
- High and low pressure gauges
- DVVF and DVV2F devices for low air temperature operation
- Hydronic module with 1 or 2 pumps, high or low head. Buffer tank available.
- Anti-intrusion grills